Micro-Scissor Lift

Upright POWERED ACCESS



MX19 micro-scissor lift specifications

	MX19 MICRO-SCISSOR LIFT
max. working height A	7.8m
max. platform height B	5.8m
max. drive height	5.8m
platform capacity (SWL)	227kg
platform size (inside - with deck ex	xtended) 0.72m x 2.54m
stowed height C	2.13m
with guardrails lowered	1.6m
stowed length D	1.75m
with steps removed	1.6m
width E	0.76m
gross weight	1,460kg
max. drive speed	3.7km/h
with platform raised	1km/h
gradeability	14°/ 25%
inside turning radius	0.15m
ground clearance	95mm
lift speed - raise/lower	19/18 seconds
drive system	dual front wheel hydraulic motors
tyres	305mm dia. solid rubber, non-marking
battery charger	25 amp 90V - 240V automatic with ammeter
parking brake	2 wheel, spring-applied hydraulic release and manual release
control system	smooth, one-hand proportional controls
power source	24V 4hp DC electric motor 4 x 6V 220 Ah batteries

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate UpRight operators manual for detailed instructions on the proper use and maintenance



Compact dimensions and tight turning radius provides excellent manoeuvrability

Upright Vigo Centre, Birtley Road, Washington,

POWERED ACCESS Tyne & Wear, NE38 9DA, U.K.

Sales Tel: +44 (0) 845 1550 057 • Spare Parts Tel: +44 (0) 845 1550 058


www.upright.com


standard features

- Roll-out deck extension with foot pedal release
- Folding guardrails
- Side forklift pockets
- Non-marking tyres
- Swing-out service modules
- Tilt alarm, descent alarm
- Selectable motion/alarm
- Proportional controls
- Lift-up rear guardrail to ease loading
- Ground view grates in deck extension
- AC power cable to platform
- Hour meter
- Horn, push button on controller
- 1 year parts and labour warranty
- 5 year structural warranty

options

- Platform gate interlock
- Special paint colours
- Environmental green oil





BP1. MX19 10/06





